## AMENDMENTS TO THE CLAIMS

Claim 1 (Canceled)

Claim 2 (Previously Presented): The laminate according to Claim 11, wherein each of the titanium oxide layers has a refractive index of at least 2.4 at a wavelength of 550 nm.

Claims 3-5 (Canceled)

Claim 6 (Currently Amended): The laminate according to Claim 11, wherein the sheet resistance value is from 0.5 to 3.5  $\Omega/\Box$ , the visible light transmittance is at least 40%, and the visible light reflectance is at most 10%.

Claim 7 (Previously Presented): The laminate according to Claim 11, wherein a resin film having a low-reflecting property is further laminated thereon.

Claim 8 (Previously Presented): The laminate according to Claim 11, wherein a resin film having a near-infrared shielding property is further laminated thereon.

Claim 9 (Previously Presented): The laminate according to Claim 11, wherein the visible light reflectance is at most 3%.

Claim 10 (Canceled)

Application No. 09/857,209 Reply to Final Rejection of December 22, 2004

Claim 11 (Currently Amended): A laminate which comprises

a substrate, and

7

a titanium oxide layer, a metal layer and a titanium oxide layer laminated alternately in this order on the substrate in (2n + 1) layers (wherein n is a positive integer),

wherein an interlayer having a refractive index of less than 2.4 at a wavelength of 550 nm is interposed at at least two interlaminar boundaries between the titanium oxide layer and the metal layer,

wherein each interlayer independently is a layer consisting of at least one member selected from the group consisting of a nitride, an oxynitride, a carbide, a boride, niobium oxide, GZO, and ITO,

wherein each metal layer independently is a layer containing silver as the sole or main component,

wherein the thickness of each interlayer independently is from 0.1 to 30 nm,

wherein both sides of at least one metal layer is sandwiched between interlayers,

wherein the titanium oxide layer closest to the substrate and the titanium oxide layer

furthest from the substrate each independently has a thickness of from 20 to 60 nm, and all

other titanium oxide layers each independently has a thickness of from 40 to 120 nm, and

which laminate contains at least two metal layers.

Claim 12 (Canceled)

Claim 13 (Previously Presented): The laminate according to Claim 11, which contains at least three metal layers.

Application No. 09/857,209 Reply to Final Rejection of December 22, 2004

Claim 14 (Previously Presented): The laminate according to Claim 13, which contains at least four metal layers.

Claim 15 (Previously Presented): The laminate according to Claim 11, wherein all metal layers are sandwiched between two interlayers.

Claims 16-21 (Canceled)

Claim 22 (Previously Presented): The laminate according to Claim 11, wherein each metal layer independently is a layer containing Ag-Pd alloy (0.1 to 5 atomic % Pd).

Claims 23-30 (Canceled)